



- Designed for use as an outer seal on a vinyl tape splice
- Fast-drying
- Suitable for use for direct burial and moisture protection
- Helps protect from moisture and corrosion

### [Where to Buy](#)

## Specifications

Attribute Name	Value
Application Method	Brush
Applications	Seal on vinyl tape applications which are subject to excessive amounts of oil.
Brand	3M
Can Size	15 Fluid Ounce (US)
Container Volume	65
Coverage Area	Depends on the application
Drinking Water Approvals	Not approved for potable water applications
Material	Synthetic rubber & resin
National Stock Number	5970009623335
Product Form	Liquid

Product Type	Can
RoHS 2011/65/EU Compliant	Yes
RoHS EU Comments	RoHS 2011/65/EU compliant without exemption <a href="#">*Important RoHS information</a>
Shelf Life	2 Year
Storage Temperature	10 to 27 Degree Celsius, < 75 % RH
Trademark	Scotch
Volume (metric)	426 ml

## Details

- Designed for use as an outer seal on a vinyl tape splice
- Fast-drying
- Suitable for use for direct burial and moisture protection
- Helps protect from moisture and corrosion
- 15-oz can
- RoHS 2011/65/EU Compliant
- 10/case

3M™ Scotchkote™ Electrical Coating FD is a fast-drying sealant that is designed to improve the weather resistance of taped splices.

3M™ Scotchkote™ Electrical Coating FD is designed to use with Scotch® Vinyl Electrical Tapes. It is ideal for use in applications that are subjected to excessive amounts of moisture and oil. RoHS Compliant.