

3M™ Temflex™ Rubber Splicing Tape 2155, 3/4 in x 22 ft, Black, 20 rolls/case

3M ID HC000592382



- Rubber resin provides excellent adherence
- Self-fusing rubber backing offers durability and resists tears as well as abrasion
- Tape measures 3/4 in x 22 ft x 30 mil
- Comes in black color

Specifications

Attribute Name	Value
Adhesive Material	Rubber Resin
Agency Approvals	UL Listed, UL Listed, File E129200
Applications	Electrical Maintenance
Backing Material	Rubber

Backing Thickness (Metric)	0.76 mm
Brand	Temflex™
Breaking Strength	9 lb/in
Case Quantity	12 Rolls
Color	Black
Dielectric Strength (V/mil)	600
Elongation	700 %
Elongation at Break	7
Family	3M™ Temflex™ Rubber Splicing Tape 2155
Gel Time	28 Minutes at 140°F (60°C)
High Temperature Rating	176°F (80°C)
Insulated	Yes
Length	22 Linear Foot
Length (Metric)	6.7 m
Liner/Linerless	Liner
Material	EPR with Liner
Maximum Operating Temperature (Celsius)	80 Degree Celsius
Maximum Operating Temperature (Fahrenheit)	176 Degree Fahrenheit
Operating Temperature (Fahrenheit)	Up to 176 °F
Product Markets	Electrical Construction, Electrical MRO, Power Distribution
Product Type	Rubber and Splicing Tapes
RoHS 2011/65/EU Compliant	Yes
RoHS EU Comments	RoHS 2011/65/EU compliant without exemption *Important RoHS information

Self-extinguishing	No
Self-sticking	Yes
Shelf Life	3 Year
Suitable for High Voltage	No
Tape Color	Black
Tape Grade	General Use
Tape Length (Metric)	6.7 m
Tape Type	General Use Rubber Tape
Tape Width (Metric)	19 mm

Details

- Rubber resin provides excellent adherence
- Self-fusing rubber backing offers durability and resists tears as well as abrasion
- Tape measures 3/4 in x 22 ft x 30 mil
- Comes in black color
- Withstands temperatures up to 176 degrees F (80 degrees C)
- UL Listed and RoHS 2011/65/EU Compliant
- 20 rolls/case, BULK

3M™ Temflex™ Tape 2155 is a 30-mil, general purpose, highly conformable, electrically insulating, low-voltage rubber splicing tape. The self-fusing tape is designed to offer guaranteed performance when used with solid dielectric cable insulations and has a liner, which will not stick to the tape upon unwind. It withstands a wide temperature range of 176 degrees F (80 degrees C).

3M™ Temflex™ Splicing Tape 2155 with self-fusing rubber backing, has rubber-resin adhesive that offers optimized adherence. This tape is designed for low-voltage electrical insulating and moisture-sealing applications. It maintains the flexibility over a wide range of temperatures. Electrical insulating tape finds application in bolted connections, service drops, lightning connections, ground rod connections and motor leads. UL Listed and RoHS 2011/65/EU Compliant.