

## **General Purpose Terminals**

Quick and reliable crimp-type wire connections.

- Color-coded by wire gauge size.
- Available in a variety of packaging options and stud sizes.
- Includes Spade and Ring Terminals, Disconnects, and Bullet, Butt & Tap Splices (p.17-19)

## **Spade Terminals -** Vinyl-Insulated Barrel

- Rated at 600 Volt Max.
- Temperature rating: 167 °F (75 °C).



22-18 Gauge	Part #	Pkg Qty	Stud Size
U	20-111	20/clam	4 to 6
	20-112	20/clam	8 to 10
	75-111	75/clam	4 to 6

Part #	Pkg Qty	Stud Size
10-113	100/clam	4 to 6
10-114	100/clam	8 to 10
15-114	15/clam	8 to 10
20-113	20/clam	4 to 6
20-114	20/clam	8 to 10
75-113	75/clam	4 to 6
	10-113 10-114 15-114 20-113 20-114	10-113 100/clam 10-114 100/clam 15-114 15/clam 20-113 20/clam 20-114 20/clam

12-10 Gauge	Part #	Pkg Qty	Stud Size
U	10-116	50/clam	8 to 10
	15-116	15/clam	8 to 10
	75-116	5/clam	8 to 10
	•		



## Ring Terminals - Vinyl-Insulated Barrel

• Rated at 600 Volt Max.



4 to 6

4 to 6

8 to 10

8 to 10

Stud Size

• Temperature rating: 167 °F (75 °C).









