

## Snap-In Seals (1/2" to 2")

Convenient snap-in feature for quick installation.

- Zinc-plated to resist corrosion.
- Not waterproof.

Part #	Pkg Qty	For Knockout Dia.
601	100/box	1/2"
602	100/box	3⁄4"
603	50/box	1"

## **Galvanized Hanger Strap**

For hanging or fastening conduit, pipe or cables.

• Flexible for easy use.




Fart #	F KG QLY	Description
GHS-1510	1/card	10' x ¾" x 26 gauge

(	Q	
	SEE PG	FOR MORE INFO ON KNOCKOUTS

## Saf-Te-Plate<sup>™</sup> Protectors

Protects cable and plastic pipe from nail punctures.

• Plate attaches to wood studs with a single



Part #	Pkg Qty	Description
FP159-3	100/box	1 <sup>1</sup> / <sub>2</sub> " x 3" x 16 gauge Metal Safety Plate
FP159-6	50/box	1 <sup>1</sup> / <sub>2</sub> " x 6" x 16 gauge Metal Safety Plate

## **Duct Seal Compound**

Seals conduit openings against drafts, dust, moisture and noise.

- Protects terminal boxes, pot heads and bushings from corrosive elements.
- Deadens switch gear panel noise.
- Dough-like compound is easily "thumbed" over holes and gaps.
- Will not harden or form a skin under normal conditions.
- Not for use outdoors.
- No Silicone.
- Specifications:
  - Viscosity: ASTM D-217 300-gram load 7.0 -11.0; ASTM DS-S2 100-gram load 9.0 -15.0
  - Temperature Range: Adheres at -20 °F (-29 °C). Will not slump after 1 hr. at 350 °F (175 °C).
  - Flash Point: Over 550 °F (285 °C).
  - Other Properties: Non-conducting, non-deteriorating, non-toxic, non-corrosive, non-staining, non-curable; 99% solid, coil-based.

Part #	Pkg Qty	Description
DS-130	30 pugs	1 lb Pugs
DS-530	6 pugs	5 lb Pugs



169