

Product Features

Designed for light gauge metal applications where low profile head exposure is desired. Super sharp 23° Streaker® point means quick and easy penetration into metal (25-20 ga.), while wafer head provides greater bearing surface. The right screw for K-lath installation.

Specifications:

Gauge: #8
Length: 1-in
Head Type: Wafer framing
Recess Type: #2 Phillips
Thread Type: Twin lead
Coating: Clear zinc

Installation Guidelines:

Use a standard screw gun with a depth-sensitive nose piece. Suggested screw gun specification for optimal performance - 4 amps minimum and RPM range of 0 to 4,000.

- The wafer head is fully seated when the head is flush with the work surface.
- Overdriving my result in fastener failure or strip out of the work surface.
- The fastener must penetrate beyond the metal three full thread pitches.

All GRABBER® screw products are manufactured in facilities that are ISO 9002 and ISO 14001 certified and approved. The fasteners comply with ASTM C1513, as referenced in ICC ESR report ESR-1271, are approved for use in structures governed by the International Building Code 2006, 2009, 2012, International Residential Building Code 2006, 2009, and 2012.

Fastener Classification	Light Gauge Metal (20-25)
Fastener Head	Wafer
Fastener Drive	#2 Phillips
Fastener Length	1"
Fastener Gauge	#8
Fastener Point	Streaker
Fastener Package Type	Packaged Screws
Fastener Package Weight	Mini Pack
Approx. Pcs.	50
Fastener TPI	15
Fastener Coating	Clear Zinc
Fastener Color	Gray