

Item #	Style	Description	1-9	10-24	25-99	100+
<b>700 - 2700 MHz DAS Ceiling Mount Antennas</b>						
The HyperLink® high performance broadband / multi-band ceiling mount DAS antennas are designed to operate from 700 MHz to 3 GHz. These high performance antennas are specifically designed to distribute Cellular and WiFi signals throughout a building or area. The Multi-Band design of this antenna eliminates the need to purchase different antennas for each frequency.						
HG2404CU-NF	L	800 MHz-3.0 GHz, 3.5 dBi, Ceiling Mount DAS Antenna, N Female Connector	25.95	24.39	22.84	CALL
HG2404CU-RSP	L	800 MHz-3.0 GHz, 3.5 dBi, Ceiling Mount DAS Antenna, RP-SMA Plug Connector	25.95	24.39	22.84	CALL
HG2404CU-RTP	L	800 MHz-3.0 GHz, 3.5 dBi, Ceiling Mount DAS Antenna, RP-TNC Plug Connector	25.95	24.39	22.84	CALL
HG72704CU-NF	L	700 MHz-3/4 dBi, Ceiling Mount DAS Antenna, N Female Connector	36.35	33.44	30.53	CALL
HG72704CU-RSP	L	700 MHz-3/4 dBi, Ceiling Mount DAS Antenna, RP-SMA Plug Connector	36.35	33.44	30.53	CALL
HG72704CU-RTP	L	700 MHz-3/4 dBi, Ceiling Mount DAS Antenna, RP-TNC Plug Connector	36.35	33.44	30.53	CALL

## 2.4 GHz / 2.4-5.8 GHz Ceiling Antennas - Indoor Single Band / Dual Band / MIMO Antennas

HyperLink® offers a number of Ceiling Antennas in 2.4 GHz and 2.4/5.8 GHz frequencies for many indoor applications. The coverage is 360° and operating with single feed (1 X 1) as well as the new MIMO Multiple feeds (3 X 3 and 6 X 6). MIMO antennas provide the user with a single antenna to couple with the many multiple feed wireless radios operating in 802.11a/b/g/n.

### 2.4 GHz MIMO Spatial Diversity Ceiling Antennas

HG2403-SDC-3NF	J	3 dBi, Spatial Diversity Ceiling Antenna, (3) N Female Connectors	58.19	55.86	53.53	CALL
HG2403-SDC-3NM	J	3 dBi, Spatial Diversity Ceiling Antenna, (3) N Male Connectors	58.19	55.86	53.53	CALL
HG2403-SDC-3RSP	J	3 dBi, Spatial Diversity Ceiling Antenna, (3) RP-SMA Plug Connectors	58.19	55.86	53.53	CALL
HG2403-SDC-3RTP	J	3 dBi, Spatial Diversity Ceiling Antenna, (3) RP-TNC Plug Connectors	58.19	55.86	53.53	CALL

### 2.4 - 5.8 GHz Dual Band MIMO Spatial Diversity Ceiling Antennas

HG2458-3SDC-3NF	J	3 dBi, Dual Band Spatial Diversity, (3) N Female Connectors	58.19	54.70	51.21	CALL
HG2458-4SDC-6NF	K	4 dBi, Dual Band Spatial Diversity, (6) N Female Connectors	87.31	82.07	76.83	CALL
HG2458-4SDC-6NM	K	4 dBi, Dual Band Spatial Diversity, (6) N Male Connectors	87.31	82.07	76.83	CALL
HG2458-4SDC-6RSP	K	4 dBi, Dual Band Spatial Diversity, (6) RP-SMA Plug Connectors	87.31	82.07	76.83	CALL
HG2458-4SDC-6RTP	K	4 dBi, Dual Band Spatial Diversity, (6) RP-TNC Plug Connectors	87.31	82.07	76.83	CALL

### 2.4 - 5.8 GHz Dual Band Ceiling Antennas

HG2458CU-NF	L	3 dBi, Dual Band Ceiling Antenna, N Female Connector	46.75	43.01	39.27	CALL
HG2458CU-RTP	L	3 dBi, Dual Band Ceiling Antenna, RP-TNC Plug Connector	46.75	43.01	39.27	CALL

### Mounting Brackets for Antennas, Amplifiers and Surge Protectors

L-com offers an extensive line of mounting bracket options for its antennas, amplifiers, and surge protectors. Options include wall mount, window mount, mast mount and more. Visit us online at [L-com.com](http://L-com.com) for complete bracket dimensions and specifications.

HGX-LPMOUNT01	ALQ2-NMNFBS Surge Protector Mounting Bracket	5.99	5.51	5.03	CALL
HGX-PMT02	Indoor Antenna Mounting Kit, Small Metal Tilt & Swivel	11.99	11.03	10.07	CALL
HGX-PMT03	Indoor Antenna Mounting Kit, Medium Plastic Tilt & Swivel	13.99	12.87	11.75	CALL
HGX-PMT04	Large Metal Tilt & Swivel Mounting Bracket for Wall or Mast Mounting	22.99	21.15	19.31	CALL
HGX-PMT06	60° Tilt & Swivel Mounting Kit for Mounting to 1.25" to 2" Dia. Masts	10.95	10.07	9.20	CALL
HGX-PMT07	Stationary Mounting Kit for Mounting to 1.25" to 2" Dia. Masts	6.99	6.43	5.87	CALL
HGX-PMT08	Suction Cup Window Mounting Kit for Select HyperLink Antennas	11.99	11.03	10.07	CALL
HGX-PMT11	Heavy Duty Stationary Mast Mounting Kit for Mounting to 1.25" to 2" Dia. Masts	12.99	11.95	10.91	CALL
HGX-PMT14	Mast Mount Kit for Outdoor Filters/Splitters 1.25" to 2" Dia. Masts	14.95	13.75	12.56	CALL
HGX-PMT15	Indoor Antenna Mounting Kit - Compact Metal Tilt & Swivel	11.99	11.03	10.07	CALL
HGX-PMT23	Heavy Duty Angled Mast Antenna Mount	10.95	10.07	9.20	CALL
HGX-PMT26	Antenna Array Pole Mount Kit for 120 Degree Sectorial Antennas	129.95	119.55	109.16	CALL
HGX-PMT27	Antenna Array Pole Mount Kit for 90 Degree Sectorial Antennas	149.95	137.95	125.96	CALL
HGX-PMT31	Sector Panel Antenna Replacement Mounting Hardware	54.95	50.55	46.16	CALL
HGX-MMOUNT01	Ratchet Style Marine Antenna Mount	14.95	13.75	12.56	CALL
HGX-UMOUNT	Powder Coated Galvanized Steel "DSS-style" Arm-Outdoor Wall Mounting 21"	17.99	17.27	16.55	CALL
HGX-UMOUNT-10PK	Powder Coated Galvanized Steel "DSS-style" Arm-Outdoor Wall Mounting 10 Pack	137.99	132.47	126.95	CALL
HGX-UMOUNT01	Powder Coated Galvanized Steel "DSS-style" Arm-Outdoor Wall Mounting 26.7"	18.99	18.23	17.47	CALL
HGX-UMOUNT01-10PK	Powder Coated Galvanized Steel "DSS-style" Arm-Outdoor Wall Mounting 10 Pack	149.99	143.99	137.99	CALL
HGX-UMOUNT02	Ceiling/Wall Mount for 4.5" Sq. and 8.5" Sq. Patch Antennas	17.99	17.27	16.55	CALL
HGX-UMOUNT04	Universal Corner Mounting Bracket	28.99	27.83	26.67	CALL
HGX-UMOUNT07	Universal Tube Antenna/Satellite Dish Mount	26.99	25.91	24.83	CALL

### RET/AISG 8-Pin FS1 Type Male or Female Connectors

Remote Electrical Tilt (RET) antenna systems are designed so that wireless providers can make adjustments remotely to their antenna systems. The Antenna Interface Standards Group (AISG) has created specifications for the control interface for these types of systems. L-com now offers these FS1 type connectors for AISG applications as well as industrial control applications.

AISGM-2000	RET/AISG 8-Pin FS1 Type Connector, Male	13.99	13.43	12.87	CALL
AISGF-2000	RET/AISG 8-Pin FS1 Type Connector, Female	13.99	13.43	12.87	CALL

### RET/AISG 6-Conductor Control Cable Assemblies

L-com's 6-Conductor Remote Electrical Tilt (RET)/AISG compatible control cable assemblies are terminated with Male and Female FS1 type DIN connectors. The connectors on these cable assemblies are interchangeable with Amphenol C 901 A/B/C and Binder 423 series connectors.

CA-AISG6MFM01	RET/AISG 6-Conductor Control Cable, Male/Female, 1.0m	59.00	57.23	55.46	CALL
CA-AISG6MFM02	RET/AISG 6-Conductor Control Cable, Male/Female, 2.0m	62.90	61.01	59.13	CALL
CA-AISG6MFM03	RET/AISG 6-Conductor Control Cable, Male/Female, 3.0m	66.80	64.80	62.79	CALL
CA-AISG6MFM04	RET/AISG 6-Conductor Control Cable, Male/Female, 4.0m	71.90	69.74	67.59	CALL
CA-AISG6MFM05	RET/AISG 6-Conductor Control Cable, Male/Female, 5.0m	75.70	73.43	71.16	CALL
CA-AISG6MFM06	RET/AISG 6-Conductor Control Cable, Male/Female, 6.0m	79.60	77.21	74.82	CALL
CA-AISG6MFM09	RET/AISG 6-Conductor Control Cable, Male/Female, 9.0m	92.60	89.82	87.04	CALL
CA-AISG6MFM10	RET/AISG 6-Conductor Control Cable, Male/Female, 10.0m	97.65	94.72	91.79	CALL
CA-AISG6MFM15	RET/AISG 6-Conductor Control Cable, Male/Female, 15.0m	117.00	113.49	109.98	CALL
CA-AISG6MFM20	RET/AISG 6-Conductor Control Cable, Male/Female, 20.0m	136.30	132.21	128.12	CALL
CA-AISG6MFM30	RET/AISG 6-Conductor Control Cable, Male/Female, 30.0m	176.30	171.01	165.72	CALL
CA-AISG6MFM40	RET/AISG 6-Conductor Control Cable, Male/Female, 40.0m	214.90	208.45	202.01	CALL
CA-AISG6MFM50	RET/AISG 6-Conductor Control Cable, Male/Female, 50.0m	254.80	247.16	239.51	CALL
CA-AISG6MFM60	RET/AISG 6-Conductor Control Cable, Male/Female, 60.0m	293.50	284.69	275.89	CALL

Item #	Description	List Price
--------	-------------	------------

### 6-Conductor RET/AISG Control Cable by the Meter

L-com now offers 6-Conductor Remote Electrical Tilt (RET) control cable, by the meter.

CA-AISG6-METER	6-Conductor Control Cable, per Meter	3.99
----------------	--------------------------------------	------

