| Item #                                 | Description   | 1-9                     | 10-24                   | 25-99                   | 100+                 |
|--|---|-------------------------|-------------------------|-------------------------|----------------------|
| Switching Power                        | er Supplies   |                         |                         |                         |                      |
| PS909-21R                              | 9 VDC @ 1A (9W), 2.1mm DC Plug  | 10.30                   | 9.89                    | 9.48                    | CALL                 |
| PS1212-21R<br>PS1224-21R<br>PS1240-21R | 12 VDC @ 1A (12W), 2.1mm Right Angle DC Plug<br>12 VDC @ 2A (24W), 2.1mm Right Angle DC Plug<br>12 VDC @ 3.33A (40W), 2.1mm Right Angle DC Plug | 13.40<br>15.00<br>22.00 | 12.86<br>14.40<br>21.12 | 12.33<br>13.80<br>20.24 | CALL<br>CALL<br>CALL |
| PS1566                                 | 15 VDC @ 4.4A (66W), 2.1mm DC Plug  | 90.00                   | 86.40                   | 82.80                   | CALL                 |
| PS4848-25R<br>PS4870-25R               | 48 VDC @ 1A (48W), 2.5mm Right Angle DC Plug<br>48 VDC @ 1.5A (70W), 2.5mm Right Angle DC Plug  | 24.95<br>60.80          | 24.45<br>58.37          | 23.95<br>55.94          | CALL<br>CALL         |
| Lighter Plug to                        | 2.1mm Right Angle DC Plug, 3A Fuse  |                         |                         |                         |                      |
| PS-LIGHTER-06                          | Cigarette Plug to 2.1mm Right Angle DC Plug, 3A Fuse, 6ft (1.8m)  | 10.00                   | 9.60                    | 9.20                    | CALL                 |
| Accessories                            |   |                         |                         |                         |                      |
| PSX-EU1<br>PSX-EU2                     | US Flat or Euro Round to Euro 4.8mm Round A/C Adapter<br>EU 4/4.8mm Round to US NEMA 6-15R Flat A/C Adapter                                     | 4.00<br>4.00            | 3.60<br>3.60            | 3.20<br>3.20            | CALL<br>CALL         |
| PSCORD2<br>PSCORD3                     | 2 Conductor Plug, USA/AC Power Cord, 1.0ft (0.3m)<br>3 Conductor Plug, USA/AC Power Cord, 1.0ft (0.3m)  | 4.00<br>3.48            | 3.84<br>3.34            | 3.68<br>3.20            | CALL<br>CALL         |
| Item #                                 | Description   |                         |                         | Lis                     | st Price             |
| PLANET 802.3a                          | t/af PoE Extenders  |                         |                         |                         |                      |

## PLANET 802.3at/af PoE Extenders

PLANET's POE-PTE101 and POE-PTE201 are simple devices designed to extend both the reach of Ethernet Data and IEEE 802.3at/802.3af Power over Ethernet over the standard 100m (328ft.) Cat5e/6 UTP cable to 200m, 300m or more. The POE-PTE101 is for use with standard Ethernet while the POE-PTE201 is designed for use with Gigabit applications.

| POE-PTE101 | IEEE 802.3af Power over Ethernet Extender            | 60.00 |
|------------|--|-------|
| POE-PTE201 | IEEE 802.3at/af Power over Gigabit Ethernet Extender | 81.00 |

## **PLANET 151 Series PoE Injector and Splitters**

The PLANET POE-PT151 is an IEEE 802.3af Power over Ethernet Injector that provides DC 48V over Ethernet Cat5 cables. This provides power to 802.3af PoE capable devices. For non-PoE capable devices, the POE-PT151S splits the power and data from the Cat5 cable allowing these devices to operate within a PoE based network. The POE-PT151S ships with two power cables with 2.0mm and 2.5mm female power connectors.

| P0E-PT151  | 48 VDC, PoE Injector, Includes Power Supply | 42.00 |
|------------|---|-------|
| P0E-PT151S | 5V/12V, PoE Splitter, Includes Power Cables | 31.00 |

## PLANET 12 and 24 Port PoE Injector Hubs

The PLANET POE-PT1200 and POE-PT2400 are 12-port and 24-port IEEE 802.3af Power over Ethernet injector hubs that comply with IEEE 802.3, IEEE 802.3u and IEEE 802.3af standards. Equipped with 12 or 24 10/100BASE-TX Fast Ethernet ports, the products support full 48 VDC power for any remote IEEE802.3af powered devices. These hubs feature Web and Console management interfaces to allow administrators easy management access. **NOTE:** CANNOT BE USED WITH CISCO PoE PRODUCTS.

PDE-PT1200 48 VDC, 12 Port PDE Injector Hub 280.00 PDE-PT2400 48 VDC, 24 Port PDE Injector Hub 430.00





