

Item #	Description	1-9	10-24	25-99	100+
--------	-------------	-----	-------	-------	------

Domestic and International Power Cords - UL/CSA or European Approved

L-com stocks several popular external power cords for domestic, international and medical applications. All assemblies are fully molded and meet the required safety specifications.

Domestic LSZH Power Cords - UL/CSA Approved

LSZH (Low Smoke Zero Halogen) Versions of our Standard North American N5/15 to C13 Power cords in 2 & 3 meter lengths. Available in three gauges 18 AWG, 16 AWG & 14 AWG to meet your particular power requirements.

LCPWR18Z-2M	LSZH Power Cord SJE3 - 18 AWG, N5/15 - C13 Black, 2m (6.6ft)	14.98	14.38	13.78	CALL
LCPWR18Z-3M	LSZH Power Cord SJE3 - 18 AWG, N5/15 - C13 Black, 3m (9.8ft)	19.98	19.18	18.38	CALL
LCPWR16Z-2M	LSZH Power Cord SJE3 - 16 AWG, N5/15 - C13 Black, 2m (6.6ft)	15.98	15.34	14.70	CALL
LCPWR16Z-3M	LSZH Power Cord SJE3 - 16 AWG, N5/15 - C13 Black, 3m (9.8ft)	21.98	21.10	20.22	CALL
LCPWR14Z-2M	LSZH Power Cord SJE3 - 14 AWG, N5/15 - C13 Black, 2m (6.6ft)	20.98	20.14	19.30	CALL
LCPWR14Z-3M	LSZH Power Cord SJE3 - 14 AWG, N5/15 - C13 Black, 3m (9.8ft)	27.98	26.86	25.74	CALL

Domestic Power Cords - UL/CSA Approved

Connector options include N1/15 to C7, N5/15 to Regular and Locking C13 and pigtail end. Heavy duty 18 AWG cable, color is Black.

PCM1000	Power Cord SPT2 - 18 AWG, N1/15 - C7 Black, 2m (6.6ft)	3.95	3.79	3.63	CALL
PCM1010	Power Cord SVT3 - 18 AWG, N5/15 - Pigtail Black, 2m (6.6ft)	4.95	4.75	4.55	CALL
PCM1012	Power Cord SVT3 - 18 AWG, N5/15 - C13 Black, 2.3m (7.6ft)	5.95	5.71	5.47	CALL
PCM1014	Power Cord SJT3 - 18 AWG, N5/15 - C13 Black, 3m (9.8ft)	6.95	6.67	6.39	CALL
LC-PWRN15LK-6	Locking IEC Power Cord SJT3 - 18 AWG, N5/15 - Locking C13 Black, 1.8m (6.0ft)	8.75	8.40	8.05	CALL

Hospital Grade Power Cords - UL/CSA Approved

Connector options are Hospital Grade N5/15 Molded Gray/Clear and Black to Regular and Locking C13. Heavy duty 18 AWG cable, colors are Gray and Black.

PCM1050	Power Cord SJT3 - 18 AWG, N5/15 - Hospital Grade Gray Mold - C13 Gray, 3.1m (10.0ft)	9.45	9.07	8.69	CALL
PCM1052	Power Cord SJT3 - 18 AWG, N5/15 - Hospital Grade Clear Mold - C13 Gray, 3.1m (10.0ft)	9.45	9.07	8.69	CALL
LC-PWRN15HLK-10	Locking IEC Cord SJT3 - 18 AWG, N5/15 Hospital Grade - Locking C13 Black, 3.1m (10.0ft)	17.95	17.23	16.51	CALL

International Power Cords - Meets VDE and Several Other Approvals

Connector options are CEE 7/7 to C13, EN50075/XVI (CEE 7/16 "Europlug" Type C) to C7 and BS1363 to Locking C13, color is Black.










PCM1020	Power Cord H05VVF3G - 18 AWG, CEE 7/7 - C13 Black, 2.5m (8.2ft)	7.95	7.63	7.31	CALL
PCM1030	Power Cord H03VH2F2 - 21 AWG, CEE 7/16 - C7 Black, 1.8m (6.0ft)	6.95	6.67	6.39	CALL
LC-PWREUOLK-2M	Locking IEC Power Cord H05VVF3G - 18 AWG, CEE 7/7 - Locking C13 Black, 1.8m (6.0ft)	11.35	10.90	10.44	CALL
LC-PWRUKLK-2M	Locking IEC Power Cord H05VVF3G - 21 AWG, BS1363 - Locking C13 Black, 1.8m (6.0ft)	13.15	12.62	12.10	CALL

Universally Approved Jumper Cords - Domestic and European Approved, UL/CSA, VDE

Connector options are C14 to Regular and Locking C13, heavy duty 18 AWG cable, color is Black.

PCM1040	Power Cord SJT3 - 18 AWG, C14 - C13 Black, 1m (3.3ft)	4.95	4.75	4.55	CALL
PCM1042	Power Cord SJT3 - 18 AWG, C14 - C13 Black, 2m (6.6ft)	5.95	5.71	5.47	CALL
PCM1044	Power Cord SJT3 - 18 AWG, C14 - C13 Black, 3m (9.8ft)	6.95	6.67	6.39	CALL
LC-PWRC14LK-6	Locking IEC Power Cord SJT3 - 18 AWG, C14 - Locking C13 Black, 1.8m (6.0ft)	11.35	10.90	10.44	CALL

Power Cord Identification Guide

  CEE 7/16 "Europlug"	 NEMA 1/15 Polarized	 NEMA 5/15	 NEMA 5/15 Hospital Grade	  CEE 7/7 "Schuko" BS1363 "UK"	  C13 C14
---	---	---	--	---	--

Switching Power Supplies, Power Cords, PoE Power Supplies and Lighter Power Adapters

We offer a broad range of switching power supplies which support 110/220 VAC operation. Models in this series include 9 VDC, 12 VDC, 15 VDC and 48 VDC options. Additionally, PoE power supplies are available which provide data and power over a single Cat5 cable to end devices which are compliant with IEEE standard PoE pinout (Pins 4 & 5 Power +/Pins 7 & 8 Power -).

Switching Power Supplies

PS909-21R	9 VDC @ 1A (9W), 2.1mm DC Plug	10.30	9.89	9.48	CALL
PS1212-21R	12 VDC @ 1A (12W), 2.1mm Right Angle DC Plug	13.40	12.86	12.33	CALL
PS1224-21R	12 VDC @ 2A (24W), 2.1mm Right Angle DC Plug	15.00	14.40	13.80	CALL
PS1240-21R	12 VDC @ 3.33A (40W), 2.1mm Right Angle DC Plug	22.00	21.12	20.24	CALL
PS1566	15 VDC @ 4.4A (66W), 2.1mm DC Plug	90.00	86.40	82.80	CALL
PS4820-POE-1	48 VDC @ 20W, Dual RJ45 Jacks	25.00	23.50	22.00	CALL
PS4870-25R	48 VDC @ 1.5A (70W), 2.5mm Right Angle DC Plug	60.80	58.37	55.94	CALL
PS4848-25R	48 VDC @ 1A (48W) 2.5mm Right Angle DC Plug	24.95	24.45	23.95	CALL
PS4860-POE	48 VDC @ 1.25A (60W), Dual RJ45 PoE, Requires PSCORD3	80.00	75.20	70.40	CALL

Lighter Plug to 2.1mm Right Angle DC Plug, 3A Fuse

PS-LIGHTER-06	Cigarette Plug to 2.1mm Right Angle DC Plug, 3A Fuse, 6ft (1.8m)	10.00	9.60	9.20	CALL
---------------	--	-------	------	------	------

12 Volt to 48 Volt DC/DC Boost Converter (Regulator)

The PC12480.8 DC-to-DC Converter is designed to convert 12VDC (12-26) battery voltage to 48VDC @ 0.85A. It is ideal for mobile applications that require 48VDC electronic equipment to be powered by converting the 12VDC (12-26) power from most cars, trucks or aircraft.

PC12480.8	12 Volt to 48 Volt DC/DC Boost Converter (Regulator)	55.00	52.80	50.60	CALL
-----------	--	-------	-------	-------	------

Accessories

PSX-EU1	US Flat or Euro Round to Euro 4.8mm Round Pins A/C Adapter	4.00	3.60	3.20	CALL
PSX-EU2	EU 4/4.8mm Round to US NEMA 6-15R Flat Blades A/C Adapter	4.00	3.60	3.20	CALL
PSCORD2	2 Conductor Plug, USA/AC Power Cord, 1ft (0.3m)	4.00	3.84	3.68	CALL
PSCORD3	3 Conductor Plug, USA/AC Power Cord, 1ft (0.3m)	3.48	3.34	3.20	CALL

