

## **AC Horsepower Ratings**

**At Rated Voltage:** 2 HP L-L / 1 HP L-N

## **Electrical Specifications**

**Amperage:** 20 A

**Current Interrupting:** Certified for current interrupting at full rated current

**Dielectric Voltage:** Withstands 2000V per UL498

**Grounding:** Grounding

**Pole:** 3

**Temperature Rise:** Max 30C after 250 cycles OL at 200 percent rated current

**Voltage:** 125/250 VAC

**Wire:** 4

## **Environmental Specifications**

**Environment:** Dry

**Flammability:** Rated HB or better UL94

**Operating Temperature:** -40°C to 60°C

## **Material Specifications**

**Assembly Screws:** Steel, Zinc Plated

**Back Cover:** Thermoplastic

**Blades/Contacts:** Solid Brass

**Body Material:** Impact Modified Nylon

**Clamp Insert:** Nylon

**Color:** Black-White

**Cord-Clamp:** Nylon

**Terminal Screws:** Brass

**Wire Module:** Nylon

## **Mechanical Specifications**

**Cord Range:** 0.560 to 0.775

**Product ID:** Ratings are permanently marked on device

**Terminal Accom.:** 18-10 AWG

**Terminal ID:** Brass-Hot, Green-Ground, Silver-Neutral

**Wire Gauge:** 14-10 AWG

## **Product Features**

**Brand:** Black and White

**Color:** Black-White

**Device Type:** Locking Plug

**NEMA:** L14-20P

## **Standards and Certifications**

**ANSI:** C-73

**CSA C22.2 No. 42:** File LR-406

**NEMA:** WD-6

**NOM:** 057

**UL Fed Spec WC-596:** File E13393

**UL498:** File E13393

**Warranty:** Limited Lifetime Warranty