

### **Electrical Specifications**

**Amperage:** 30/50 A

**Current Interrupting:** Certified for current interrupting at full rated current

**Dielectric Voltage:** Withstands 2000V per UL498

**Grounding:** Non-Grounding

**Pole:** 3

**Temperature Rise:** Max 30C after 50 cycles OL at 150 percent rated current

**Voltage:** 125/250 VAC

**Wire:** 3

### **Environmental Specifications**

**Flammability:** Rated V-2 per UL 94

**Operating Temperature:** -40°C to 60°C

### **Material Specifications**

**Assembly Screws:** Steel, Zinc Plated

**Blades/Contacts:** Brass

**Body Material:** Thermoplastic

**Color:** Black

### **Mechanical Specifications**

**Cord Range:** .687 - 1.050

**Product ID:** Ratings and NEMA I.D. permanently marked on device

**Terminal Accom.:** 10-6 AWG

**Terminal ID:** Brass-Hot, Green-Ground, Silver-Neutral

### **Product Features**

**Color:** Black

**NEMA:** 10-30P/10-50P

**Voltage:** 125/250 VAC

### **Standards and Certifications**

**ANSI:** C-73

**CSA C22.2 No. 42:** File LR-406

**NEMA:** WD-6

**NOM:** 057

**UL498:** File E13393

**Warranty:** 2-Year Limited