

## **AC Horsepower Ratings**

**At Rated Voltage:** 2 HP

## **Electrical Specifications**

**Amperage:** 30 A

**Current Limiting:** Full Rated Current

**Dielectric Voltage:** Withstands 2000V per UL498

**Grounding:** Non-Grounding

**Pole:** 3

**Temperature Rise:** Max 30C after 50 cycles OL at 150 percent rated current

**Voltage:** 125/250 VAC

**Wire:** 3

## **Environmental Specifications**

**Flammability:** Rated V-2 per UL 94

**Operating Temperature:** -40°C to 60°C

## **Material Specifications**

**Body Material:** Thermoplastic

**Color:** Black

**Face Material:** Thermoplastic

**Strap Material:** Galvanized Steel

## **Mechanical Specifications**

**Product ID:** Ratings are permanently marked on device

**Terminal Accom.:** Up to 4 AWG

**Terminal ID:** Brass-Hot, Green-Ground, Silver-Neutral

## **Product Features**

**Amperage:** 30 A

**Color:** Black

**NEMA:** 10-30R

**Voltage:** 125/250 VAC

## **Standards and Certifications**

**ANSI:** C-73

**CSA C22.2 No. 42:** File 152105

**NEMA:** WD-6

**NOM:** 057

**UL498:** File E13399

**Warranty:** 10-Year Limited