

Technical Information

Electrical Specifications

- **Grounding:** Grounding
- **Amperage:** 15 Amp
- **Voltage:** 125 Volt
- **Pole:** 2
- **Wire:** 3
- **Temperature Rise:** Max 30C after 250 cycles OL at 200 percent rated current
- **Dielectric Voltage:** Withstands 2000V per UL498
- **Current Interrupting:** Certified for current interrupting at full rated current

Environmental Specifications

- **Flammability:** Rated HB or better UL94
- **Operating Temperature:** -40C to 60C

Material Specifications

- **Body Material:** Impact Modified Nylon
- **Back Cover:** Thermoplastic
- **Wire Module:** Nylon
- **Cord-Clamp:** Nylon
- **Clamp Insert:** Nylon
- **Blades/Contacts:** Solid Brass
- **Terminal Screws:** Brass
- **Assembly Screws:** Steel, Zinc Plated

Mechanical Specifications

- **Terminal ID:** Brass-Hot, Green-Ground, Silver-Neutral
- **Terminal Accom.:** 18-10 AWG
- **Product ID:** Ratings and NEMA I.D. permanently marked on device
- **Cord Range:** .245 - .700

Product Features

- **NEMA:** 5-15R
- **Color:** Black-White

Standards and Certifications

- **NEMA:** WD-6
- **ANSI:** C-73
- **UL 498:** File E13399
- **UL Fed Spec WC-596:** File E13393
- **CSA C22.2 No. 42:** File LR-406
- **NOM:** 057
- **Warranty:** Lifetime Warranty