

Technical Information

Electrical Specifications

- **Amperage:** 15 A
- **Current Interrupting:** Certified for current interrupting at full rated current
- **Dielectric Voltage:** Withstands 2000V per UL498
- **Grounding:** Grounding
- **Pole:** 2
- **Temperature Rise:** Max 30C after 250 cycles OL at 200 percent rated current
- **Voltage:** 125 VAC
- **Wire:** 3

Environmental Specifications

- **Environment:** Dry
- **Flammability:** Rated HB or better UL94
- **Operating Temperature:** -40°C to 60°C

Material Specifications

- **Assembly Screws:** Steel, Zinc Plated
- **Back Cover:** Thermoplastic
- **Blades/Contacts:** Solid Brass
- **Body Material:** Impact Modified Nylon
- **Clamp Insert:** Nylon
- **Color:** Black-White
- **Cord-Clamp:** Nylon
- **Terminal Screws:** Brass
- **Wire Module:** Nylon

Mechanical Specifications

- **Cord Range:** 0.240 to 0.680
- **Product ID:** Ratings and NEMA I.D. permanently marked on device
- **Terminal Accom.:** 18-10 AWG
- **Terminal ID:** Brass-Hot, Green-Ground, Silver-Neutral

Product Features

- **Brand:** Black and White
- **Color:** Black-White
- **Device Type:** Straight Blade Plug
- **Feature:** Angled
- **NEMA:** 5-15P

Standards and Certifications

- **ANSI:** C-73
- **CSA C22.2 No. 42:** File LR-406
- **NEMA:** WD-6
- **NOM:** 057
- **UL 498:** File E13399
- **UL Fed Spec WC-596:** File E13393
- **Warranty:** Lifetime Warranty