


## Ground Clamp for Armored Wire



### Use:

Ground clamps are used to connect bare or armored copper wire to galvanized steel water pipe. Pressure bar grips armored wire insulation to decrease chances of grounding conductor being pulled out. Can be used with copper ground rod.

- For copper rod 1/2"-1"

### Material:

- Copper Alloy

### Standards:

UL 467  
CSA C22.2 No. 41  
NEC Article 250

### Certifications:


UL E88878 SP LR57925

Model Number	UPC (0-31857)	Trade Size	Product Dimensions (inches)			Retail Pack Quantity	Master Case Quantity
			A	B	C		
Polybag							
41409	414092	1/2" - 1"	2.25	1.35	0.67	1	12

Trade Size	Pipe Range	Wire Range	Copper Rod Range
1/2" - 1"	1/2" - 1"	#8 - #4	1/2" - 1"

**⚠ WARNING:** This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.P65WARNINGS.ca.gov](http://www.P65WARNINGS.ca.gov). Wash hands after handling.

## Ground Clamp with Lay-In Lug



### Use:

Ground clamps with lay-in lug are used to connect a ground wire in Rigid conduit or Rebar to copper or galvanized steel water pipe.

- Suitable for direct burial in ground and concrete

### Material:

- Copper Alloy

### Standards:

UL 467  
CSA C22.2 No. 41  
NEC Article 250

### Certifications:

UL E88878

### US Patent No.:

6976857

Model Number	UPC (0-31857)	Trade Size	Product Dimensions (inches)			Retail Pack Quantity	Master Case Quantity
			A	B	C		
Polybag							
42309	423094	1/2" - 1"	2.28	1.50	0.95	1	20

Trade Size	Pipe Range	Wire Range	Rebar Range
1/2" - 1"	1/2" - 1"	#10 - #2	3/8" - 1"

**⚠ WARNING:** This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.P65WARNINGS.ca.gov](http://www.P65WARNINGS.ca.gov). Wash hands after handling.