


Compression Connector



Use:

Compression type connectors are used to secure and terminate steel EMT conduit to a knockout in a metal box or enclosure. For dry location applications.

- Concrete-tight
- 2-1/2" and 3" also listed for Rigid conduit or IMC

Material:

- Zinc Die-Cast
- Zinc-Plated Steel

Standards:

UL 514B
CSA C22.2 No. 18.3-12

Certifications:

Die-Cast:  E210498 (1/2" - 2")
E155411 (2-1/2" - 3")

 LR57925

Steel:  E210498

Model Number	UPC (0-31857)	Trade Size	Product Dimensions (inches)			Retail Pack Quantity	Master Case Quantity
			A	B	C		

Die-Cast

Polybag

49250	492502	1/2"	1.19	0.98	0.38	1	50
18021	180218	1/2"	1.19	0.98	0.38	3	10
44250	442507	1/2"	1.19	0.98	0.38	5	15
49251	492519	3/4"	1.29	1.22	0.41	1	25
18023	180232	3/4"	1.29	1.22	0.41	2	5
44251	442514	3/4"	1.29	1.22	0.41	5	5

Boxed - Individual UPC

55252M	111298	1"	1.48	1.52	0.55	1	10
02-55252	552527	1"	1.48	1.52	0.55	1	10
55253M	111304	1-1/4"	1.70	1.85	0.61	1	5
02-55253	552534	1-1/4"	1.70	1.85	0.61	1	8
55254M	111311	1-1/2"	1.86	2.15	0.62	1	5
02-55254	552541	1-1/2"	1.86	2.15	0.62	1	5
55255M	111328	2"	2.13	2.59	0.76	1	5
02-55255	552558	2"	2.13	2.59	0.76	1	5
02-55256	552565	2-1/2"	2.62	3.15	1.02	1	5
02-55257	552572	3"	2.70	3.97	1.04	1	2

Bulk - No Individual UPC

55250	552503	1/2"	1.19	0.98	0.38	50	10
55251	552510	3/4"	1.29	1.22	0.41	25	10

Contractor Pack

TC-601	652500	1/2"	1.19	0.98	0.38	50	2
TC-602	652517	3/4"	1.29	1.22	0.41	25	2

Steel

Polybag

49030	490300	1/2"	1.31	1.05	0.50	1	10
46030	460303	1/2"	1.31	1.05	0.50	5	20
49031	490317	3/4"	1.48	1.28	0.52	1	12
46031	460310	3/4"	1.48	1.28	0.52	5	10

Boxed - Individual UPC

02-54532	545321	1"	1.53	1.56	0.64	1	20
02-54533	545338	1-1/4"	1.70	1.94	0.68	1	10
02-54534	545345	1-1/2"	1.96	2.17	0.72	1	5
02-54535	545352	2"	2.07	2.68	0.72	1	5

