


Plastic Insulating Bushing



Use:

Plastic insulating bushings are used on the end of Rigid conduit, IMC and other threaded connectors to provide a smooth, well-rounded bearing surface to protect wires or cables.

- Rated 105°C
- Flame retardant

Material:

- Non-Metallic

Standards:

UL 514B
CSA C22.2 No. 18
NEMA FB-1

Certifications:

UL US E121487

Model Number	UPC (0-31857)	Trade Size	Product Dimensions (inches)			Retail Pack Quantity	Master Case Quantity
			A	B	C		
Polybag							
49321	493219	1/2"	1.05	0.36	0.60	2	100
47321	473211	1/2"	1.05	0.36	0.60	1	50
47322	473228	3/4"	1.29	0.40	0.78	1	50
49322	493226	3/4"	1.29	0.40	0.78	2	50
49323	493233	1"	1.63	0.49	1.00	1	25
49324	493240	1-1/4"	1.93	0.48	1.30	1	25
49325	493257	1-1/2"	2.18	0.48	1.52	1	25
49326	493264	2"	2.64	0.54	1.95	1	25
49327	493271	2-1/2"	3.25	0.63	2.33	1	10
49328	493288	3"	3.90	0.68	2.90	1	10
Bulk - No Individual UPC							
55321	553210	1/2"	1.05	0.36	0.60	100	10
55322	553227	3/4"	1.29	0.40	0.78	100	10
55323	553234	1"	1.63	0.49	1.00	50	10
55326	553265	2"	2.64	0.54	1.95	50	1