

Specifications

Assembled Product Dimensions (L x W x H)

2.50 x 2.50 x 7.79 Inches

Directions

Instructions

Directions for Use: Before attempting to start engine, spray starting fluid into the air cleaner or intake air stream for 2-3 seconds (no more than 3 seconds), stand clear of engine, then start engine. Do Not let can contact battery terminal or starter solenoid. Do Not spray while ignition is on or cranking. Do Not use product to mount or seal tires. Attention: Before use, read and follow engine owner/operator manual recommendations. Improper use and use in some glow-plug-equipped diesels could result in engine damage and/or bodily harm.

Safe Handling Instructions

DANGER: EXTREMELY FLAMMABLE. VAPORS MAY CAUSE FLASH FIRE. VAPORS HARMFUL. EXCESSIVE INHALATION MAY BE FATAL. MAY CAUSE EYE AND SKIN IRRITATION. MAY BE HARMFUL OR FATAL IF SWALLOWED. CONTENTS UNDER PRESSURE. Keep away from heat, sparks and open flames. DO NOT smoke. Extinguish all flames and pilot lights, turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. DO NOT let can contact battery terminals or starter solenoid. DO NOT use product to mount or seal tires. Use only with adequate ventilation. Avoid breathing high concentrations of vapor. Deliberate inhalation of the contents of this can is extremely dangerous and may be fatal. Avoid contact with eyes and prolonged or repeated contact with skin. DO NOT puncture or incinerate container. DO NOT expose to direct sunlight or other sources of heat or store at temperatures above 120°F (49°C). Wash hands after using product. KEEP OUT OF THE REACH OF CHILDREN. CONTAINS: HEPTANE (CAS 142-82-5), DIETHYL ETHER (CAS 60-29-7), CARBON DIOXIDE (CAS 124-38-9), PROPANE (CAS 74-98-6), N-BUTANE (106-97-8). This diesel fuel additive complies with the federal low sulfur content requirements for use in diesel motor vehicles and non-road engines. FIRST-AID: EYES: Flush with large amounts of water. Get medical attention if irritation persists. SKIN: Wash exposed areas with soap and water. INHALATION: If affected, remove to fresh air. IF SWALLOWED: DO NOT induce vomiting. Call a physician or poison control center immediately for instructions.

Warnings

Warning Text

DANGER: EXTREMELY FLAMMABLE. VAPORS MAY CAUSE FLASH FIRE. VAPORS HARMFUL. EXCESSIVE INHALATION MAY BE FATAL. MAY CAUSE EYE AND SKIN IRRITATION. MAY BE HARMFUL OR FATAL IF SWALLOWED. CONTENTS UNDER PRESSURE. Keep away from heat, sparks and open flames. DO NOT smoke. Extinguish all flames and pilot lights, turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. DO NOT let can contact battery terminals or starter solenoid. DO NOT use product to mount or seal tires. Use only with adequate ventilation. Avoid breathing high concentrations of vapor. Deliberate inhalation of the contents of this can is extremely dangerous and may be fatal. Avoid contact with eyes and prolonged or repeated contact with skin. DO NOT puncture or incinerate container. DO NOT expose to direct sunlight or other sources of heat or store at temperatures above 120°F (49°C). Wash hands after using product. KEEP OUT OF THE REACH OF CHILDREN. CONTAINS: HEPTANE (CAS 142-82-5), DIETHYL ETHER (CAS 60-29-7), CARBON DIOXIDE (CAS 124-38-9), PROPANE (CAS 74-98-6), N-BUTANE (106-97-8). This diesel fuel additive complies with the federal low sulfur content requirements for use in diesel motor vehicles and non-road engines. FIRST-AID: EYES: Flush with large amounts of water. Get medical attention if irritation persists. SKIN: Wash exposed areas with soap and water. INHALATION: If affected, remove to fresh air. IF SWALLOWED: DO NOT induce vomiting. Call a physician or poison control center immediately for instructions.