

Fluoroelastomer (FPM, FKM, Viton®) O-Rings

Fluorocarbon FKM & Viton® O-Rings: Chemical resistant Fluorocarbon FKM O-Rings exhibit exceptional resistance to chemicals, oils, temperature extremes, low compression set, low gas permeability and excellent aging characteristics. It has a good resistance to ozone, high temperatures, oxygen, mineral oil, synthetic hydraulic fluids, fuels, aromatics and many organic solvents and chemicals.

Applications include: Hydraulic Oil, Petroleum Base, Silicone oil and grease, Mineral and vegetable oil and grease, Aliphatic hydrocarbons (fuel, butane, propane, natural gas), Aromatic hydrocarbons (benzene, toluene), Chlorinated hydrocarbons (trichlorethylene and carbon tetrachloride), Chlorine Water, Gasoline, Fuels, Liquefied Petroleum Gas (LPG), Natural Gas, Propane, Diesel Oil, High vacuum, ozone and weather.

Avoid: Ketones, hot water, steam, Brake Fluid, alkalis, and Skydrol® fluids, Ammonia gas, amines, alkalis, Skydrol 500, Methyl Ethyl Ketone (MEK), Low molecular organic acids (formic and acetic acids)

Designed to meet or exceed the properties of these popular FKM Compounds: V747-75, V700-75, 19357, V14-75, 9009-75, F13664, 514AD and 9500-75

Operating temperature: -20° to +400F°

- V75 -Chemical Resistant Black 75 Duro - [AS-568 FKM O-Rings \(Stock\)](#) | [Metric FKM O-Rings \(Stock\)](#)
- BV75 - Chemical Resistant Brown 75 Duro - [AS-568 FKM O-Rings \(Stock\)](#) | [Metric FKM O-Rings \(4-6 Weeks\)](#)
- GV75 - Chemical Resistant Green 75 Duro - [AS-568 FKM O-Rings \(Stock\)](#) | [Metric FKM O-Rings \(8-10 Weeks\)](#)
- V90 - Chemical Resistant Black 90 Duro - [AS-568 FKM O-Rings \(Stock\)](#) | [Metric FKM O-Rings \(8-10 Weeks\)](#)
- FDABV75 - Chemical Resistant Brown FDA 3A 75 Duro - [AS-568 FKM O-Rings \(Stock\)](#) | [Metric FKM O-Rings \(10-14 Weeks\)](#)
- V75-MS - Mil-Spec Chemical Resistant Black 75 Duro - [AS-568 FKM O-Rings \(Stock\)](#)
- CV75 Viton® Extreme Chemical Resistant ETP 75 Duro - [AS-568 O-Rings \(Stock\)](#) | [Metric O-Rings \(4-6 Weeks\)](#)
- V60 - Chemical Resistant Black 60 Duro - [AS-568 O-Rings \(6-8 Weeks\)](#) | [Metric O-Rings \(10-12 Weeks\)](#)
- BV60 - Chemical Resistant Brown 60 Duro - [AS-568 O-Rings \(6-8 Weeks\)](#) | [Metric O-Rings \(10-12 Weeks\)](#)

- FDARV - Chemical Resistant Red FDA 3A 75 Duro - [AS-568 O-Rings \(6-8 Weeks\)](#) | [Metric O-Rings \(10-14 Weeks\)](#)
- V75-UL - UL Approved For Fuel/Alcohol Black 75 Duro - [AS-568 O-Rings \(6-8 Weeks\)](#) | [Metric O-Rings \(10-14 Weeks\)](#)
- V75-GFLT - Viton GFLT® FKM Black 75 Duro - [AS-568 O-Rings \(8-10 Weeks\)](#)
- V95-RGD - Rapid Gas Decompression FKM 95 Duro - [AS-568 O-Rings \(8-10 Weeks\)](#)